

Dry Wipers STERILE



50% Rayon/50% Polyester Spunlace Blend.
Suited for ISO Class 5 or higher cleanroom environments where sterility is required.

Product Qualities

- Continuous filament Rayon/Polyester spunlace blend for a clothlike feel
- No binders or surfactants, resulting in low extractables
- High water absorbency rate, plus excellent absorption efficiency and capacity
- Compliant with AAMI Guidelines
- Gamma irradiated to a 10⁶ Sterility Assurance Level (SAL)
- Double-bagged with case liner
- Certificate of Conformity available online at www.kcprofessional.com
- Certificate of Irradiation (COI) on each case and available online at www.kcprofessional.com

Product Specifications

| Characteristic | Specification Target |
|--|--|
| Particle Generation | |
| Biaxial Shake, particles ≥ 0.5 microns | 15.1 x 10 ⁶ /m ² |
| Biaxial Shake, fibers ≥ 100 microns | 263 x 10 ³ /m ² |
| Total Extractables | |
| Deionized Water, g/m ² | 0.03 |
| Isopropyl Alcohol (IPA, isopropanol), g/m ² | 0.01 |
| Ions | |
| Sodium (Na ⁺), ppm | 11.1 |
| Potassium (K ⁺), ppm | 2.5 |
| Chloride (Cl ⁻), ppm | 10 |
| Absorbency | |
| Absorbent Capacity, ml/m ² | 395 |
| Absorbency Rate, seconds | 1.0 |

All tests performed in accordance with IEST RP-CC004.3.

| | Code | Cleanroom Class ISO FS209 | Delivery System | Color | Material | Size W x L | Case Content |
|--------------------|------|------------------------------|-------------------|-------|-----------------|---------------|---------------|
| STERILE CL5 | 7655 | 5 100 | Flat / Double Bag | ○ | Rayon/Polyester | 30.5 x 30.5cm | 25 x 20 = 500 |

TECHNICAL INFORMATION SERVICE

Fax or e-mail your enquiry
We will respond within one working day

00 800 00 35 45 65



infofax@kcc.com



® Registered Trademark or * Trademark of Kimberly-Clark Worldwide, Inc.
© 2006 KCWW. All Rights Reserved.
4329.01 GB 08.06