



KLEENGUARD* G10 GREY NITRILE GLOVES PRODUCT SPECIFICATION

SIZE/CATALOG:	X-Small	Small	Medium	Large	X-Large
	97820	97821	97822	97823	97824

REQUIREMENTS:

1. Style

- Grey Nitrile
- Powder Free
- Non-Sterile
- Beaded Cuff
- Textured Fingertips
- Ambidextrous

2. Barrier

- Freedom from holes (e.g. pinholes) at AQL₁ 4.0

3. Strength

		<u>Before Aging</u>		<u>After Aging</u>	
		Tensile Strength	Ultimate Elongation	Tensile Strength	Ultimate Elongation
		(MPa)	(%)	(MPa)	(%)
	28 min.		500 min.	22 min.	450 min.

As measured by ASTM D412, Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers – Tension. Aged according to ASTM D573, Standard Test Method for Rubber – Deterioration in an Air Oven.

4. Dimensions

- Dimensional characteristics at AQL₁ 10.0. Palm widths +/-10.

<u>Palm Width (mm) – nominal values</u>					<u>Thickness (mm)</u>	<u>Length (mm)</u>
X-Small	Small	Medium	Large	X-Large	Palm	
70	80	95	110	120	0.09 min	240 min
					Finger 0.08 min	
					Cuff 0.06 min	

As measured by ASTM D6319, Standard Practice for Nitrile – Measurement of Dimensions

5. Packaging

- 150 gloves (140 for XL) per dispenser box.
- 10 dispenser boxes per case.
- Shipping case and inner packaging labeled with product name, size, lot/batch and catalog number

1. AQL levels defined according to ISO 2859-1 for sampling by attributes.

Kimberly Clark Professional*
1400 Holcomb Bridge Road • Roswell, Georgia
(800)255-6401 • www.kcprofessional.com

KleenGuard
BRAND

