



KIMBERLY-CLARK PROFESSIONAL\*  
 1400 Holcomb Bridge Road  
 Roswell, Georgia  
 (800) 851-7538

[www.kcprofessional.com](http://www.kcprofessional.com)

## KLEENGUARD\* N95/FFP1 Molded Particulate Respirator with Comfort Strap and Dual Valves

### Product Information

Code	Respirator Class	Protection Level	Features
64260	M10	NIOSH <b>N95</b> EN149:2001 <b>FFP1</b>	Dual exhalation valves, Blue, Wide comfort head strap with adjustable attachment

### Features

- Meets requirements for NIOSH N95 (42 CFR 84) and EN149:2001 filtering facepiece respirators.
  - Filters at least 95% of 0.3 micron particles at 85 liters per minute flow rate (NIOSH N95)
  - Filters at least 80% of 0.6 micron particles at 95 liters per minute flow rate (EN149:2001)
  - NIOSH certification TC 84A-4638
- Soft cloth covered foam nose seal
- Wide nonwoven elastic laminate head strap
- Head strap is adjustable
- Adjustable nose wire to provide a good seal around the nose.



### Materials

- KLEENGUARD\* respirators are free of natural rubber latex
- Polyester inner and outer shells
- Electrostatic-treated polypropylene meltblown filtration layer
- Nonwoven elastic laminate head strap
- Aluminum nose wire attached with EVA hot melt adhesive
- ABS exhalation valves with silicone rubber diaphragms
- Nose seal made of gray PVC closed cell foam with adhesively laminated polyester cloth covering

### Packaging

Code	Respirators per Box	Box Size LxWxH	Boxes per Case	Case Size (OD) LxWxH	Respirators per Case
64260 N95/FFP1 with valves	10	140 x 130 x 220 mm 5.51" x 5.12" x 8.63"	8	465 x 300 x 285mm 18.25" x 11.9" x 11.25"	80