



KIMBERLY-CLARK PROFESSIONAL*
 1400 Holcomb Bridge Road
 Roswell, Georgia
 (800) 851-7538

www.kcprofessional.com

KLEENGUARD* N95/FFP1 Molded Particulate Respirators

Product Information

Code	KLEENGUARD* Respirator Class	Protection Level	Features
64230	M10	NIOSH N95 EN149:2001 FFP1	Blue head strap
64240	M10	NIOSH N95 EN149:2001 FFP1	Blue head strap Exhalation Valve

Features

- Meets requirements for NIOSH N95 (42 CFR 84) and EN149:2001 filtering facepiece respirators.
 - Filters at least 95% of 0.3 micron particles at 85 liters per minute flow rate (NIOSH N95)
 - NIOSH certification TC 84A-4539 for code 64230 N95 (no valve)
 - NIOSH certification TC 84A-4543 for code 64240 N95 with valve
- Soft foam nose seal
- Woven elastic head straps. Blue head strap color indicates M10 respirators.
- Head straps are ultrasonically bonded to the mask. No staples.
- Adjustable nose wire to provide a good seal around the nose.

Materials

- KLEENGUARD* Respirators are free of natural rubber latex
- Polyester inner and outer shells
- Electrostatically-treated polypropylene meltblown filtration layer
- Woven polyester elastic headband
- Aluminum nose wire attached with EVA hot melt adhesive
- 64240 valved respirator has ABS exhalation valve with silicone rubber diaphragm
- Nose seal of gray closed cell foam

Packaging

Code	Respirators per Box	Box Size L x W x H	Boxes per Case	Case Size (OD) L x W x H	Respirators per Case
64230 N95/FFP1	20	140 x 130 x 200 mm 5.51 x 5.12 x 7.87"	8	420 x 310 x 280 16.6 x 11.90 x 11.1"	160
64240 N95/FFP1 with valve	10	140 x 130 x 160 mm 5.51 x 5.12 x 6.30"	8	345 x 310 x 280 13.6 x 12.3 x 11.1"	80



Exhalation valve – enhanced comfort through heat and moisture reduction