



KIMBERLY-CLARK PROFESSIONAL*
 1400 Holcomb Bridge Road
 Roswell, Georgia
 (800) 851-7538

www.kcprofessional.com

KLEENGUARD* R95 Molded Particulate Respirators

Product Information

Code	KLEENGUARD* Respirator Class	Protection Level	Features
64410	M20	NIOSH R95	Yellow head strap Exhalation Valve

Features

- Meets requirements for NIOSH R95 (42 CFR 84) filtering facepiece respirators.
 - Filters at least 95% of 0.3 micron particles at 85 liters per minute flowrate (NIOSH R95)
 - **Oil resistant for up to 8 hours of usage**
 - NIOSH certification TC 84A-4545
- Soft foam nose seal
- Woven elastic head straps. Yellow head strap color indicates M20 respirators.
- Head straps are ultrasonically bonded to the mask. No staples.
- Adjustable nose wire to provide a good seal around the nose.

Materials

- KLEENGUARD* Respirators are free of natural rubber latex
- Polyester inner and outer shells
- Electrostatically treated polypropylene meltblown filtration layer
- Woven polyester elastic headband
- Aluminum nose wire attached with EVA hot melt adhesive
- ABS exhalation valve with silicone rubber diaphragm
- Nose seal made of gray closed cell foam

Packaging

Code	Respirators per Box	Box Size L x W x H	Boxes per Case	Case Size (OD) L x W x H	Respirators per Case
64410 R95	10	140 x 130 x 160 mm 5.51 x 5.12 x 6.30"	8	345 x 310 x 280 13.6 x 12.3 x 11.1"	80

