



## Product Data Sheet

### Attributes & Properties<sup>◇</sup>

<b>Name:</b>	<b>85SP INTREPID<sup>®</sup> Filtration Media</b>
<b>Color:</b>	<b>Yellow / White</b>
<b>Basis Weight:</b>	<b>4.70 ounces per square yard (159 grams / square meter)</b>
<b>Efficiency:</b>	<b>87.0 %</b> <small>TSI Model 8130 automated filter tester with 0.1 <math>\mu</math>m count median diameter NaCl particles at 85 liters per minute.</small>
<b>Air Permeability:</b>	<b>60 cubic feet of air/minute per square foot of media (0.30 cubic meter of air / second per square meter of media)</b> <small>Textest FX 3300 Labotester III</small>
<b>Thickness:</b>	<b>0.150 inches (3.81 millimeters)</b> <small>Testing load of 0.025 psi (172.4 Pascals)</small>
<b>Inside Core: Diameter</b>	<b>3 inches (76.2 millimeters)</b>
<b>Roll Length:</b>	<b>250 linear yards (229 linear meters)</b>

---

<sup>◇</sup> Unless otherwise noted, the material described in this document is available for commercial sale and sold with a limited warranty. Kimberly-Clark Corporation and/or Kimberly-Clark Worldwide retains all intellectual property rights to this material, including trademarks and trade names. If the material described is defined as developmental, the material properties are estimates only and are not warranted by Kimberly-Clark Corporation.

